



# Bi-axial Machine

## FEATURES

- HIGHLY ADVANCED WITH WORLD CLASS TECHNOLOGY FULLY AUTOMATIC
- INDEPENDENT TEMPERATURE & TIMING FOR EACH ARM
- SPECIAL ARRANGEMENT FOR DOUBLE / TRIPLE LAYER TANK
- VARIABLE SPEED A C DRIVE FOR MAJOR & MINOR AXIS.
- AVAILABLE WITH INTER - CHANGEABLE STRAIGHT AND OFFSET ARM
- AVAILABLE IN TURRET TYPE & CAROUSEL TYPE



## BI-AXIAL MACHINE 3 ARMS

MODEL NO	MAXIMUM SWING DIA	PRODUCTION CAPACITY/ SHIFT	NUMBER OF ARMS STR - OFF	HEATING SYSTEM	COOLING SYSTEM	CONNECTED LOAD IN HP	REQUIRED SPACE IN MTR L X W X H
SM/3A - 150	1.5 MTR	25000 LTRS	2 + 1	GAS / DIESEL	AIR	15 HP	8 X 5 X 3
SM/3A - 210	2.1 MTR	30000 LTRS	2 + 1	GAS / DIESEL	AIR & WATER	21 HP	10 X 7 X 3.5
SM/3A - 280	2.8 MTR	45000 LTRS	2 + 1	GAS / DIESEL	AIR & WATER	27 HP	12 X 10 X 4
SM/3A - 320	3.2 MTR	75000 LTRS	2 + 1	GAS / DIESEL	AIR & WATER	35 HP	15 X 12 X 5

## BI - AXIAL MACHINE 2 ARMS

MODEL NO	MAXIMUM SWING DIA	PRODUCTION CAPACITY/ SHIFT	NUMBER OF ARMS STR - OFF	HEATING SYSTEM	COOLING SYSTEM	CONNECTED LOAD IN HP	REQUIRED SPACE IN MTR L X W X H
SM/2A - 150	1.5 MTR	20000 LTRS	1 + 1	GAS / DIESEL	AIR	12 HP	6 X 3 X 2.5
SM/2A - 210	2.1 MTR	25000 LTRS	1 + 1	GAS / DIESEL	AIR & WATER	17 HP	8 X 5 X 3



BURNER